

Brick Clean 10%

Technical Specification

Brick Acid, Concrete Cleaner / Remover

BRICK CLEAN 10 % is a selected blend of inorganic acids for the removal of light mortar splashes from brickwork and rust from a wide range of surfaces
Brick Clean 10% was also developed for the removal of stains, grime, rust, algae and lime scale from a wide range of paving surfaces.

Advantages

- Removal of grime and algae..
- Removal of mortar stains and efflorescence from masonry.
- Removal of rust stains from concrete surfaces.
- Used by brush or spray & easily rinsed away
- Removal of rust and scale from metal components.
- Final washing of exposed aggregate panels.

Application

Cleaning of brickwork:

For removal of mortar splashes, saturate the area with water and apply the BRICK CLEAN 10 % neat, then lightly wire brush and rinse with water. Heavy mortar deposits may require application of BRICK CLEAN 30 %

Cleaning of Paths and Patio surfaces

General use – 2 parts Brick Clean 10% to 1 part water. Severe staining – undiluted

Limestone, terrazzo, other sensitive surfaces – 1 part Brick Clean 10% to 3 parts water or weaker.

Handling:

Brick Clean 10% is an acid based cleaner and precautions against accidental contact should be taken. **Cleaning** After use rinse all tools with water.

Protective gloves and safety glasses are recommended. Avoid contact with skin and eyes.

Clothing may be damaged by prolonged contact. If exposed, remove and rinse thoroughly in water. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

Keep out of the reach of children.

Application:

Brush area to be cleaned well to remove dust, loose dirt and other material that would absorb Brick Clean 10% unnecessarily. Thoroughly saturate the area with water. Apply the Brick Clean 10% diluted as recommended to an inconspicuous area as a test to check the strength is not too high. If action is satisfactory apply generally using brush or spray. Take care not to allow spray onto other surfaces, cars etc. Leave for 1 hour then brush with a stiff brush. Rinse with plenty of clean water and allow to dry. Stubborn deposits may require repeated application of Brick Clean

When used on pigmented surfaces some colour loss may occur. If in doubt about the quantity or dilution required for a given finish then we recommend a small trial in an inconspicuous area.

Storage


The BRICK CLEAN 10 % container should be sealed after use to prevent evaporation. BRICK CLEAN 10 % corrodes most metals, including stainless steel and certain GRP depending upon the resin. Store in supplied container only. Store small containers away from reactive materials.

Shelf Life

Practically unlimited in sealed containers.

Specification

BRICK CLEAN 10 % is supplied by Simply Precast Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department



Health and Safety

Eyes:

Immediately flood eyes with lots of water while lifting the eyelids. Continue to rinse and get immediate medical attention.

Skin:

Immediately wash with water, preferably under a shower, removing contaminated clothing while washing. Get medical attention if blistering occurs.

Inhalation:

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Get prompt medical attention.

Ingestion:

Do not induce vomiting.

Get medical attention immediately.

Wash out mouth with water.

Give plenty of water to drink.

See Safety Data Sheet for further information.